





LevALERT Model 9700

Bin Level Indicators

FULL OR LOW, LEVALERT LETS YOU KNOW.
In one quick glance, know the level of material in your bin.



**REMAINS BLACK
WHEN MATERIAL IS
BELOW INDICATOR**



**ROTATES TO YELLOW
WHEN MATERIAL IS AT
OR ABOVE INDICATOR**

TOP BENEFITS



STAY SAFE

Know your bin levels from the ground. Avoid climbing dangerous bin ladders and stairs.



PLANNING AID

Install indicators to provide a signal on when to stop filling, order product, turn on a motor, etc.



DEPENDABLE

You can trust our bin level indicators to work all of the time, in even the harshest of conditions. **5 year warranty!**



HIGHLY VISIBLE

Premium 3M reflective indicator easily visible day or night from over 300 feet.



NO ELECTRICITY NEEDED

Completely mechanical operation. Automatically resets.



EASY INSTALLATION

Install our bin level indicators in under 5 minutes from the outside of the bin.

PREMIUM MATERIALS

1

Corrosion resistant, UV stable, high strength plastic components. **Won't fade or crack, and lens won't yellow!**

2

Premium 3M reflective indicator. **Easily visible from over 300 feet!**

3

Hermetically sealed lens to body. **No condensation.**

4

Moisture-proof bin seal. **Seals indicator to the bin!**

5

Activator frame secures tight to bin wall. **Material does not accumulate behind activator.**

6

Wear resistant Teflon coated fabric used for the activator. **Reduces abrasion & provides years of problem-free use!**







LevALERT Model 9700

Bin Level Indicators

COMMON BIN TYPES




POPULAR USES



LEVALERT MODEL 9700

BEST SELLER!



PRODUCT HIGHLIGHTS



Extra large indicator for high visibility

Activator frame stays tight to bin wall.
Ideal for high shear load applications
and use with grain spreaders.

5" or 7" Activator Width



Manufactured by
LevALERT, Inc.
Minnetonka, MN
levalert.com

OPTIONS

PART NUMBER	WEIGHT RANGE	GREAT FOR
9700-7 7" Activator width	10-55 lbs. / cubic foot tolerance	Great for corn, oats, sunflowers, ground feeds, grass seeds
9700-5 5" Activator width	55-100 lbs / cubic foot tolerance	Great for fertilizer, sand, salt, and cement powders

9700 Specifications


Installs on outside of bin, corrugated
or flat wall bin styles up to 3/8" in
thickness.

Operates effectively at temperatures
between +180F (82C) to -30F (-35C).

Pat. 10,408,659, Pat. 10,557,740, Pat.
D848,874

5 Year Warranty on Bin Level
Indicators.

OPTIONAL MICRO-SWITCH



Expand the Indicator's
capabilities by performing
an electrical operation.
Simply add the optional Micro-
Switch to turn off and on
motors or lights, sound a horn
or alarm, etc.

ITEM ID	DESCRIPTION	TECHNICAL SPECIFICATIONS
A91	Micro-Switch Only	AC/DC, contains both NO/NC circuitry
A92 (AC or DC)	Micro-Switch / Relay Kit	Switch plus AC- 120 Relay

SPDT. Rated voltage: 125 VAC 3A, 250 VAC
2A, 30 VDC 3A. **Cable length:** 12"(304 mm)
Approved Safety Standards: UL (UL1054)/
CSA (CSA C22.2 No.55). **RoSH Compliant**